



General Specifications:

VLS – Subterranean Scissors Lift

VASARI Sales **877-333-9334**

Model	Travel (inches)	Lifting Capacity (lbs.)	Lowered Height (inches)	Standard Platform w/BTG (Vehicle Clearance) (inches)	Minimum Platform w/BTG (Vehicle Clearance) (inches)	Maximum Platform w/BTG (Vehicle Clearance) (inches)	Maximum Axle Load Over End (lbs)	HP (Amp Draw) 230V 1ph	Cylinder Qty	Up Speed (seconds)	Down Speed (seconds)	Maximum Floor Pressure (psi)	Total Shipping Weight (lbs.)
96VLS70	96	7,000	20	108 x 216 (96W x 88H)	96 x 196 (84W x 88H)	120 x 222 (108W x 88H)	4,000	5 (28)	4	107	54	146	14,000
108VLS70	108	7,000	20	108 x 216 (96W x 100H)	96 x 196 (84W x 100H)	120 x 222 (108W x 100H)	4,000	5 (28)	4	120	60	146	14,000
120VLS70	120	7,000	20	108 x 216 (96W x 112H)	96 x 196 (84W x 112H)	120 x 222 (108W x 112H)	4,000	5 (28)	4	134	67	146	14,000
132VLS70	132	7,000	27	108 x 216 (96W x 124H)	96 x 216 (84W x 124H)	120 x 264 (108W x 127H)	4,000	5 (28)	4	325	163	81	16,200
144VLS70	144	7,000	29	108 x 224 (96W x 136H)	96 x 224 (84W x 136H)	120 x 264 (108W x 136H)	4,000	5 (28)	4	326	163	83	17,000
156VLS70	156	7,000	29	108 x 246 (88W x 83H)	96 x 246 (76W x 83H)	120 x 264 (100W x 83H)	4,000	5 (28)	4	435	220	87	18,100
168VLS70	168	7,000	34	108 x 216 (88W x 83H)	96 x 196 (76W x 83H)	120 x 216 (100W x 83H)	4,000	5 (28)	2	340	170	153	15,000
180VLS70	180	7,000	34	108 x 216 (88W x 83H)	96 x 196 (76W x 83H)	120 x 216 (100W x 83H)	4,000	5 (28)	2	360	180	153	15,000
192VLS70	192	7,000	34	108 x 216 (88W x 83H)	96 x 196 (76W x 83H)	120 x 216 (100W x 83H)	4,000	5 (28)	2	390	195	153	15,000